

Wiremold RC7 Multi-Service Poke-Thru Assembly, Black

Part No. RC7ATCBK



Prewired 20A duplex receptacle can be wired as standard duplex or isolated ground. Flanges available painted in gray (GY), black (BK), ivory (VY). Flanges also available in plated brushed brass (BS) and brushed aluminum (AL). Slide covers match the painted flange colors, gray, black, ivory. Aluminum and brass flanges shipped with black slide cover. Brass flange also available with nonmetallic brass colored slide holder (AB). Aluminum flange also available with nonmetallic aluminum color slide holder (AA). Includes Wiremold Open System unloaded inserts. NOTE: Includes two Cat 6 TechChoice discrete keystone connectors, two Ortronics TracJack adapters, and two Wiremold Open System adapters. RC7 Series Poke-Thru Devices require a 3 1/16inch (78mm) diameter hole. Not designed to work with bare concrete or terrazzo. Floor covering thickness 1/8inch minimum.

Features & Benefits

Prewired 20A duplex receptacle can be wired as standard duplex or isolated ground. Flanges available painted in gray (GY), black (BK), ivory (VY). Flanges also available in plated brushed brass (BS) and brushed aluminum (AL). Slide covers match the painted flange colors, gray, black, ivory. Aluminum and brass flanges shipped with black slide cover. Brass flange also available with nonmetallic brass colored slide holder (AB). Aluminum flange also available with nonmetallic aluminum color slide holder (AA). Includes Wiremold Open System unloaded inserts. NOTE: Includes two Cat 6 TechChoice discrete keystone connectors, two Ortronics TracJack adapters, and two Wiremold Open System adapters. RC7 Series Poke-Thru Devices require a 3 1/16inch (78mm) diameter hole. Not designed to work with bare concrete or terrazzo. Floor covering thickness 1/8inch minimum.

Specifications

| Wiremold | Color | Black |
|--|---|--|
| 786564067412 | Country Of Origin | Mexico |
| 2 | Application Sector | Commercial |
| cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT, cULus Listed Nonmetallic Outlet Boxes & Fittings Classified for Fire Resistance: File R8209 Guide CEYY Meets Article 300.21 300.22[C] &314 of NEC | Туре | Poke-Thru |
| | | |
| 7.0 in | Product Weight US | 4.34 lb |
| 784.0 cu in | Product Depth US | 16.0 in |
| | 786564067412 2 cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT, cULus Listed Nonmetallic Outlet Boxes & Fittings Classified for Fire Resistance: File R8209 Guide CEYY Meets Article 300.21 300.22[C] &314 of NEC 7.0 in | 786564067412 Country Of Origin Application Sector CULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT, cULus Listed Nonmetallic Outlet Boxes & Fittings Classified for Fire Resistance: File R8209 Guide CEYY Meets Article 300.21 300.22[C] &314 of NEC 7.0 in Product Weight US |

| Product Height US | 7.0 in | Cubic Capacity | 24.5 cu in |
|------------------------|---------------------------|-------------------------------|------------|
| Core Hole Size | 3.063 in | | |
| Listing Agencies / 3r | d Party Agencies | | |
| cULus ListingNumber | E2961 | cULus Listed | Yes |
| Buy American Act Co | ompliance | | |
| NAFTA | Yes | | |
| Additional Information | on | | |
| RoHS Conformant | Yes | Product Environmental Profile | Yes |
| Technical Informatio | n | | |
| Cable Entry | Knockouts & Conduit Stubs | Number of Outlets | 2 |
| | | | |