

Hospital-Grade Tamper-Resistant 20A Self-Test Duplex GFCI

Features & Benefits

| realures & Denemis | | | | | |
|-------------------------------|---|-----------------------|------------------------|--|--|
| Hospital Grade GFCI self-test | One-piece, brass, triple-wipe power contacts for lasting retention. | | | | |
| Specifications | | | | | |
| General Info | | | | | |
| Product Line | Pass & Seymour | Color | Black | | |
| Country Of Origin | China | Number of Receptacles | 2 | | |
| Outlet Type | Commercial, GFCI, Indoor, Self-Test, Tamper-Resistant | Application Sector | Residential/Commercial | | |
| Standard | cULus, UL Listed, FSUL | Туре | Outlet | | |
| Dimensions | | | | | |
| Product Width US | 1.73 in | Product Depth US | 1.03 in | | |
| Product Height US | 4.2 in | | | | |
| Listing Agencies / 3rd Party | Agencies | | | | |
| cULus Listed | Yes | | | | |
| Additional Information | | | | | |
| Product Environmental Profile | Yes | | | | |
| Technical Information | | | | | |
| nterrupt Rating | 4 A | Frequency Rating | 60 Hz | | |
| Trip Range | 5±1 mA | Connection | Back and Side Wire | | |

| Amperage | 20 A | Number of Poles | Double Pole |
|--------------------------|------------------------|-----------------|-------------|
| Indoor/Outdoor | Indoor | Voltage | 125.0 V |
| Environmental Conditions | 95% Humidity, UL 94 V2 | | |