



## Spec-Grade Isolated Ground Tamper-Resistant 20A Self-Test Duplex GFCI

## Features & Benefits

Spec-Grade GFCI self-test One-piece, brass, triple-wipe power contacts for lasting retention.

## Specifications

## General Info

| Product Line                          | Pass & Seymour   | Color                 | Gray                    |  |  |
|---------------------------------------|--|-----------------------|-------------------------|--|--|
| Country Of Origin                     | China  | Number of Receptacles | 2                       |  |  |
| Outlet Type                           | Commercial, GFCI, Indoor, Self-Test,<br>Tamper-Resistant | Application Sector    | Residential/Commercial  |  |  |
| Standard                              | cULus, UL Listed, FSUL                                   | Warranty Type         | 1-Year Limited Warranty |  |  |
| Туре                                  | Outlet   |                       |                         |  |  |
| Dimensions                            |  |                       |                         |  |  |
| Product Width US                      | 1.73 in  | Product Depth US      | 1.03 in                 |  |  |
| Product Height US                     | 4.2 in   |                       |                         |  |  |
| Listing Agencies / 3rd Party Agencies |  |                       |                         |  |  |
| cULus Listed                          | Yes  |                       |                         |  |  |
| Additional Information                |  |                       |                         |  |  |
| Product Environmental Profile         | Yes  |                       |                         |  |  |
| Technical Information                 |  |                       |                         |  |  |
|                                       |  |                       |                         |  |  |

| Trip Range               | 5±1 mA                 | Connection      | Back and Side Wire |
|--------------------------|------------------------|-----------------|--------------------|
| Amperage                 | 20 A                   | Number of Poles | Double Pole        |
| Indoor/Outdoor           | Indoor                 | Voltage         | 125.0 V            |
| Environmental Conditions | 95% Humidity, UL 94 V2 |                 |                    |