

Wiremold **4AT Prewired All Power Evolution™ Poke-Thru Device-Gray**Part No. 4ATCP4RGY



Designed for retrofit and new construction, Evolution Series 4" Poke-Thru devices provide convenient access to power, communications, and audio/video services recessed below floor level - providing maximum device protection. Two gangs of capacity allow you to configure services for the needs of your space. Evolution Series 4" Poke-Thru devices are the perfect fit for kiosks, training rooms, classrooms, healthcare facilities or commercial buildings with open-space architecture.

Features & Benefits

All Evolution Series Poke-Thru Devices, like every Wiremold Poke-Thru Device, meet and exceed UL scrub water exclusion requirements for tile, carpet, and wood covered floors.

Specifications

Product Line Wiremold UPC Number 786564090731 Country Of Origin United States Construction Assembled Number of Knockouts 10 Application Sector Commercial Standard CULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT. cULus Listed Nonmetallic Outlet Boxes and Fittings Classified for Fire Resistance: File R8209 Guide CEYY. Meets Article 300.21 300.22[C] and 314 of NEC. Type Poke-Thru Dimensions Product Height US 18.562 in Cubic Capacity 24.5 cu in	General Info			
Number of Knockouts 10 Application Sector Commercial cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT. cULus Listed Nonmetallic Outlet Boxes and Fittings Classified for Fire Resistance: File R8209 Guide CEYY. Meets Article 300.21 300.22[C] and 314 of NEC. Dimensions Product Width US 5.5 in Product Height US 18.562 in Cubic Capacity 24.5 cu in	Product Line	Wiremold	UPC Number	786564090731
cULus Listed Metallic Outlet Boxes: File E2961 Guide QCIT. cULus Listed Nonmetallic Outlet Boxes and Fittings Classified for Fire Resistance: File R8209 Guide CEYY. Meets Article 300.21 300.22[C] and 314 of NEC. Dimensions Product Width US 5.5 in Product Height US 18.562 in Cubic Capacity 24.5 cu in	Country Of Origin	United States	Construction	Assembled
E2961 Guide QCIT. cULus Listed Nonmetallic Outlet Boxes and Fittings Classified for Fire Resistance: File R8209 Guide CEYY. Meets Article 300.21 300.22[C] and 314 of NEC. Dimensions Product Width US 5.5 in Product Height US 18.562 in Cubic Capacity 24.5 cu in	Number of Knockouts	10	Application Sector	Commercial
Product Width US 5.5 in Product Height US 18.562 in Cubic Capacity 24.5 cu in	Standard	E2961 Guide QCIT. cULus Listed Nonmetallic Outlet Boxes and Fittings Classified for Fire Resistance: File R8209 Guide CEYY. Meets	Туре	Poke-Thru
Cubic Capacity 24.5 cu in	Dimensions			
	Product Width US	5.5 in	Product Height US	18.562 in
	Cubic Capacity	24.5 cu in		
Listing Agencies / 3rd Party Agencies				
cULus ListingNumber E2961 cULus Listed Yes	cULus ListingNumber	E2961	cULus Listed	Yes

Buy American Act Compliance				
NAFTA	Yes			
Additional Informat	ion			
RoHS Conformant	Yes	Product Environmental Profile	Yes	
Technical Informati	on			
Cable Entry	3/4 in trade size conduit for power,.75 in	Number of Outlets	4	