Pass and Seymour

15A 125V Heavy Duty Hospital-Grade Compact Duplex Receptacle, Back and Side Wire, Light Almond

Part No. 8200HLA

Heavy-Duty Hospital Grade Compact Design Duplex Receptacle Back and Side Wire 15A 125V

Features & Benefits

- Impact-resistant nylon face.
- Easily accessible break-off line contact connecting tab for split circuit wiring.
- Internal screw-pressure-plate back wire and side wire line terminals accept #14 : #10 AWG copper or copper-clad conductors.
- Auto-ground clip assures positive ground.
- Tri-drive terminal and mounting screws.
- One-piece heat-treated triple-wipe brass power contacts.
- Corrosion-resistant, zinc-plated steel strap is locked in.
- High strength thermoplastic back body.
- Compact design for easy installation.
- Temperature Rise: Maximum 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current. Operating Temperature: Maximum continuous +60°C, minimum -40°C without impact

Specifications

General Info

Product Line	Pass & Seymour	UPC Number	785007820140
Country Of Origin	Mexico	Number of Receptacles	2
Application Sector	Commercial, Hospital Grade	Standard	UL498, CSA C22.2 No. 42
Warranty Type	1-Year Limited Warranty	Type	Outlet

Dimensions

Product Width US	1.322 in	Product Depth US	0.78 in
Product Height US	3.281 in		

Listing Agencies / 3rd Party Agencies

cULus ListingNumber	140596	cULus Listed	Yes

Technical Information

Dielectric Strength	Withstands 2000V minimum	Connection	Back and side wire
Number of Wires	3	Temperature Rating	-40° - 60° C
Amperage	15 A	Number of Poles	Double Pole
Wire Size	14 - 10 AWG	Indoor/Outdoor	Indoor
Environmental Conditions	Flammability: UL94 V2		