

Wiremold AL2400 Raceway Base

Part No. AL2400B-10



6063-T5 extruded aluminum, satin anodized finish, .60" (1.5mm) nominal thickness. Packed six 10' (3m) lentghs per carton.

Features & Benefits

6063-T5 extruded aluminum, satin anodized finish, .60" (1.5mm) nominal thickness. Packed six 10' (3m) lentghs per carton.

Specifications

General Info					
Wiremold	UPC Number	786776044331			
United States	Application Sector	Commercial			
cULus Listed Raceway: File E4376 Guide RJPR. Fittings: File E41751 Guide RJPR. Raceway & Fittings: Meet Article 386 of NEC. Multioutlet Assemblies: Meet Article 380 of NEC.	Туре	Plugmold			
d Party Agencies					
E4376	cULus Listed	Yes			
ompliance					
Yes					
on					
Yes	Product Environmental Profile	Yes			
	United States cULus Listed Raceway: File E4376 Guide RJPR. Fittings: File E41751 Guide RJPR. Raceway & Fittings: Meet Article 386 of NEC. Multioutlet Assemblies: Meet Article 380 of NEC. d Party Agencies E4376 Impliance Yes	United States CULus Listed Raceway: File E4376 Guide RJPR. Fittings: File E41751 Guide RJPR. Raceway & Fittings: Meet Article 386 of NEC. Multioutlet Assemblies: Meet Article 380 of NEC. d Party Agencies E4376 CULus Listed Impliance Yes			

Lech	nical	Inforr	nation

Amperage	15 A	Enclosure Type	Aluminum
Voltage	125.0 V	Environmental Conditions	Dry interior locations