Pass and Seymour

Hard Use 20A Specification Grade Toggle Switch, Brown

Part No. CSB20AC3



Construction 3-Way Switch, Back and Side-Wire, 20A 120/277V. These switches offer excellent value while meeting federal specification standards. External screw-pressure-plate back wiring enables fast installation and superior electrical connections. Rugged construction shrugs off hard use and abuse.

Features & Benefits

One-piece brass alloy contact arm for reliable electrical performance.

One-piece steel strap with integral ground is plated for corrosion resistance.

High strength thermoplastic polycarbonate toggle resists breaking and chipping under heavy abuse.

Heavy-duty toggle bumpers for smooth and quiet operation.

Back body made of glass-reinforced nylon. Locking support provides resistance to face and back body separation.

Available with side wire or external screw-pressure-plate back and side wire models capable of accepting #14 to #10 AWG copper or copper-clad wire.

Cam designed for fast make with positive break action to minimize arcing and prolong switch life.

Oversized silver alloy contacts for longer dependable switch life.

Tri-drive terminal and mounting screws.

For covering patents, see www.legrand.us/patents.

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, click here.

Specifications

General Info

Product Line	Pass & Seymour	Color	Brown
Finish	Matte	Country Of Origin	Mexico
Application Sector	Residential/Commercial	Standard	UL Listed E140597, Standard UL20, FedSpec WS896, Flammability Rating UL94 V2
Type	Switch		

Dimensions

Product Width US	1.32 in	Product Depth US	1.073 in
Product Height US	3.281 in		

Listing Agencies / 3rd Party Agencies

cULus ListingNumber	140597	cULus Listed	Yes

Technical Information

Contact Configuration	One piece brass alloy contact arm	Actuator	Toggle
Connection	Side Wire or external screw-pressure plate	Contact Rating	Oversized silver alloy contacts
Amperage	20 A	Number of Poles	3-Way
Indoor/Outdoor	Indoor	Operating Temperature	-40°-115°C
Voltage	120/277 V	Connection Type	Wired
Degree of Protection	1500V Dielectric Withstand Voltage		