



Legrand keyed LC fiber solutions provide a simple and convenient way to physically prevent the user from making an unauthorized connection by blocking access to specific optical ports, whether they are at a workstation outlet or in a telecommunications room or data center. This is particularly important for government, finance, military and other facilities where multiple networks having different security level access requirements may be co-located.

Features & Benefits

| | |
|---|--|
| Unique Key and Color Options: Up to thirteen unique keying options/colors for a wide range of network security systems, easy identification and network management | Keyed front or Rear: Keyed LC adapters have the option to be keyed in the front only (user's side) or on both sides (user's and technician's) depending on the security requirement |
| Compatibility: All Legrand keyed LC fiber products are engineered to be compatible with other Legrand products to provide an end to end, data center to desktop solution. | Various Footprint Options: Keyed workstation adapter modules are available for TracJack® and High Density Jack (HDJ) style Face plates and surface mount boxes for complete system design flexibility. |
| Keyed workstation adapter modules are available for TracJack® and High Density Jack (HDJ) style Face plates and surface mount boxes for complete system design flexibility. | Keyed LC adapters have the option to be keyed in the front only (user's side) or on both sides (user's and technician's) depending on the security requirements. |

Specifications

General Info

| | | | |
|-------------------|-----------|------------|--------------|
| Product Line | Ortronics | UPC Number | 662875029243 |
| Country Of Origin | Mexico | Type | Adapter |

Dimensions

| | | | |
|-------------------|---------|------------------|---------|
| Product Width US | 0.62 in | Product Depth US | 1.61 in |
| Product Height US | 0.77 in | | |

Technical Information

| | | | |
|---------------|------------------------------------|--------------------|-------------|
| Compatibility | HDJ, PHDHJU | Temperature Rating | 20° - 75° C |
| Adapter Color | White | Connector Type | LC Duplex |
| Repeatability | < 0.2dB typical change,500 matings | Adapter Rear | Keyed |
| Adapter Front | Keyed | | |