



Wiremold
2000 RACEWAY BASE & COVER STAINLESS
Part No. S2000BC



Plugmold® Multioutlet Systems are available in a wide variety of lengths and fittings and in a variety of finishes to provide versatile solutions for many applications. Plugmold options include single or alternating circuits, standard or isolated ground receptacles, GFCI protection, tamper-resistant protection, USB charging, Snapicoil® harnesses of prewired receptacles, and cord-ended units. Plugmold® Multioutlet Systems are available in black or ivory ScuffCoat™ finish, painted white or gray enamel steel, stylish stainless steel, anodized aluminum and durable textured ivory nonmetallic. The painted steel product works with many types of decor and is paintable to integrate with most color schemes. Durable stainless steel and anodized aluminum Plugmold products are corrosion-resistant, making them ideal for labs.

Features & Benefits

Base – 2000B .040" (1.0mm) steel. Cover – 2000C .025" (.6mm) steel.

Specifications

General Info

| | | | |
|--------------------|---------------|-----------------------|---|
| Product Line | Wiremold | UPC Number | 786776141894 |
| Country Of Origin | United States | Number of Receptacles | 2 |
| Application Sector | Commercial | Standard | cULus Listed Base & Blank Cover: File E4376 Guide RJBTMeets Article 386 of NEC |
| Type | Plugmold | | |

Dimensions

| | | | |
|-------------------|--------|------------------|---------|
| Product Width US | 1.3 in | Product Depth US | 0.75 in |
| Product Length US | 1.3 in | | |

Listing Agencies / 3rd Party Agencies

| | | | |
|---------------------|-------|--------------|-----|
| cULus ListingNumber | E4376 | cULus Listed | Yes |
|---------------------|-------|--------------|-----|

Buy American Act Compliance

| | |
|-------|-----|
| NAFTA | Yes |
|-------|-----|

Additional Information

| | |
|-----------------|-----|
| RoHS Conformant | Yes |
|-----------------|-----|

Technical Information

| | | | |
|-------|---|------------------|-------|
| Phase | 1 | Frequency Rating | 60 Hz |
|-------|---|------------------|-------|

| | | | |
|----------------|-----------------|---------|---------|
| Enclosure Type | Stainless Steel | Voltage | 125.0 V |
|----------------|-----------------|---------|---------|

| | |
|--------------------------|------------------------|
| Environmental Conditions | Dry interior locations |
|--------------------------|------------------------|
