

Wattstopper Wattstopper PLUS Wireless Wallstation, 2 Button, Black Part No. BCS WA EN-WS-2B-ZB-BL



The WS Standard Wallstation Series consists of a two-button and a four-button wallstation that enable essential lighting control. The 2-button wallstation is a single zone manual controller ideal for conference rooms, private offices, classrooms, and other similar spaces. A short press of the upper/lower buttons turns lighting ON/OFF, while a "press and hold" dim lighting up or down. The 4-button wallstation is a single zone manual controller ideal for conference rooms, libraries, and other similar spaces. It has a dedicated button for ON, OFF, and for raise/lower functionality with intuitive button engraving. The WS Standard Series Wallstations are available in wired and wireless options.

Features & Benefits

The sleek, aesthetic designs are suitable for all interior locations

Setup and monitoring via Polaris software with easy mapping/re-mapping

10-year battery life for wireless version with automatic battery monitoring via Polaris software

Specifications

General Info				
Product Line	Wattstopper	Color	Black	
Finish	Plastic	UPC Number	840356701851	
Country Of Origin	Canada	Switch Type	Push	
Number of Switches	2	Application Sector	Commercial	
Warranty Type	5-Year	Туре	Switch	
Dimensions				
Product Width US	2.76 in	Product Weight US	0.35 lb	
Product Depth US	0.94 in	Product Height US	4.5 in	
Listing Agencies / 3rd Party Agencies				
CE Certified	Yes	FCC Compliant	Yes	

cUL Listed	Yes				
Additional Information					
RoHS Compliant	Yes	Product Has Potential to Contribute to LEED	Yes		
Technical Information					
Operating Temperature Min	-10 °C	Compatibility	Wattstopper PLUS Wireless		
Has Battery	Yes	Number of Connections	0		
Battery Capacity	3 V	Frequency Band	2.4 GHz		
Operating Temperature Max	40 °C	Number of Buttons	2		
Number of Rockers	0	Wireless Range	Zigbee, up to 100 ft		
Antenna	Integrated, Internal	Input Voltage	3 VDC		
Indoor/Outdoor	Indoor	Battery Life	Up to 10 Years		
Mounting Type	Surface	Battery	2 AA		
Operating Temperature	-10°-40°C, 14°-104°F	Operating Humidity	5-95% RH (Non- Condensing)		
Wire Connection Type	Wireless	Antenna Pattern	Omni- directional		
Engraving Type	lcon				